

PENTEK HIGH-FLOW PLEATED CARTRIDGE

NEW CONCEPT - WASHABLE PLEATED CARTRIDGE

Model No.: 5PP35
35" HF Pleated Cartridge for FRP



Pentair® Pentek® High Flow Pleated Cartridges are washable, reusable, and durable, because of this, the cartridge has an extended life span and is more economical. It also has an increased dirt holding capacity so cleaning is required less often

Applications

General water and R.O treatment
Food and beverage
Acid-base liquid in chemical processing
Industrial chemicals and organic solvents
Processing of sterile water and ultrapure water
Industrial water and plating liquid

Features

Pleated design increased surface area and contaminant removal
Longer filtration runs for fewer change-out and less maintenance
Low pressure drop
Designed for general water filtration purpose

MATERIAL OF CONSTRUCTION

Filter media: Polyester, PP, Cellulose
End cap: PP
Core: PP

PERFORMANCE

Maximum Operating Temperature: 37.8°C
Maximum Operating Pressure: 4.0 Bar

SPECIFICATION AND PERFORMANCE

*5PP35 for tank above 40"

DESCRIPTION	MODEL	LENGTH (INCH)	A ID (mm)	B OD (mm)	C LEN (mm)
PNR Pleated cartridge, 5PP35, 25/C	*5PP35	36.25"	27±1	68±1	921 ±

SL Pressure Drop vs. Flow Rate@20°C

