



BUBBLE FILTER STAINLESS SERIES

HIGH GRADE DURABLE 304 STAINLESS STEEL HOUSING

BFS-2-10-S	: BUBBLE Filter Twin 10" Stainless Steel Housing System c/w P1 10" prefilter cartridge and EPM-10 carbon block
155225-43	: PENTAIR PENTEK P1 10" Spun Bonded P.P. Cartridge
155634-43	: PENTAIR PENTEK EPM-10 10" Modified Epsilon Carbon Block Cartridge



BUBBLE Stainless Steel Filter Housing is ideal for high pressure and hot water applications with an operating pressure and temperature up to 200 psi (13.8 bar) & 200°F (93.3°C) depending on cartridge used.

Constructed with durable 304 stainless steel material for long-lasting use, it features a polished finish for a better cosmetic appearance.

The Stainless Steel Twin Water Filter Housing System is designed to deliver clean, fresh-tasting water for drinking by combining sediment and carbon filtration in a single setup. With dual housing capability, this system features:-

- Pentair P1 Prefilter Cartridge: A sediment cartridge designed to capture dirt and particulates with a nominal filtration capability of 1 micron, ensuring cleaner water and improved system performance.
- Pentair EPM-10 Carbon Block Cartridge: Effectively reduces chlorine taste and odor, ensuring clean and pleasant-tasting water.

A handle for the lock nut allows for swift cartridge replacements, while a mounting bracket provides additional stability.

For easy draining and pressure relief, a stainless steel plug is conveniently located at the bottom of the housing.

WARNING: For Drinking Water Applications, do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

FEATURES & BENEFITS

- Operating pressure and temperature up to 200 psi (13.8 bar) & 200°F (93.3°C), making it ideal for high-pressure and hot water application depending on cartridge used
- 304 stainless steel construction for long-life usage. Polished finishing for better cosmetic appearance
- Handle to lock Nut permits quick cartridge replacement
- Stainless steel plug at bottom for draining and pressure relief
- Including Pentair P1 and EPM-10 cartridge

SPECIFICATIONS

Unit Construction: 304 Stainless steel

Seal Gasket: Buna-N

Inlet / Outlet Connections: 1/2" BSPF

Drain Plug: 1/4" NPT

Max. Temperature (housing): 200°F (93.3°C)

Max. Pressure (housing): 200 psi (13.8 bar)

Dimension: L43cm x W40cm x D14cm

Cartridge #1: Pentair P1 cartridge

Cartridge#2: Pentair EPM-10 cartridge

WARRANTY

BUBBLE Division warrants to the original purchaser-consumer of its products that are free from defects in materials and workmanship for a period of one year from the date of purchase. Refer to detailed warranty statement.