

HydraSmart Series Water Softener



Automatic regeneration according to actual usage maintains quality of water



Continuous 8-steps regeneration ensures high quality water with no residues



3 adjustable salt levels allow user to minimize salt wastage and save hundreds of dollars every year



Built-in bypass feature allows flexible adjustment of water hardness and provides easy installation and maintenance

Softener Data sheet

Model	PWCE16P12	PWCE35P12	PWCE54P12
Inlet Water Condition	Chlorinated City Water		
Inlet/Outlet Pipe Size	1" BSP	1" BSP	1" BSP
Operating Pressure	20 ~ 50 PSI	20 ~ 50 PSI	20 ~ 50 PSI
Flowrate	1.1 m ³ /h	2.0 m ³ /h	3.0 m ³ /h
Total Capacity	10,000m ³	15,000m ³	20,000m ³
Resin Volume	12L	30L	40L
Salt Amount	20kg	50kg	60kg
Power Supply	220V/50Hz	220V/50Hz	220V/50Hz
Power	6W	6W	6W
Inlet Water Temp	4 ~ 38°C	4 ~ 38°C	4 ~ 38°C
Dimensions (L X W X H)	532*314*739mm	532*314*1230mm	Main Unit: 275*275*1620mm
			Salt Tank: 325*325*1000mm
Drain Line Size	1/2"	1/2"	1/2"
Salt Inlet Size	3/8"	3/8"	3/8"

