

QR2MW-7CB5-K

QL1X Manifold c/w QR2-48-P5 prefilter, 7CB5-K cartridge, WMM-W water meter, s/s mounting bracket, CPG1.4-18B pressure gauge, activation valve set (3/8") and 1/2" mini ball valve (local assembled)

DELIVERS PREMIUM QUALITY WATER FOR . . . FOUNTAIN & DRINKING WATER

For more than 75 years of experience, Everpure turns ordinary tap water into sparkling, great-tasting water for drinking, cooking and coffee making.

The Everpure QR2MW-7CB5-K System is the practical solution for filtering out disinfectant chlorine, dirt, rust, asbestos fibers, microscopic protozoan cysts and other particulates from drinking water, including oxidized iron, manganese and sulfides.



QR-P5-20: Bubble QR Cartridge w/P5-20
EV961776: 7CB5-K Replacement Cartridge

FEATURES / BENEFITS: -

- Provides clear, fresh, premium quality ingredient water for consistently great tasting coffee, tea and beverages.
- Everpure's unique carbon block reduces chlorine taste and odor and other offensive contaminants.
- Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination.
- Saves energy by reducing limescale build-up that can cause excessive machine downtime and increased maintenance costs
- Features KDF® Media which inhibits scale and microbial build up (as tested by KDF Fluid Treatment, Inc.)

The Everpure QR2MW-7CB5-K System reduces or removes the following contaminants: **

- ✓ Bad tastes and odors
- ✓ Chlorine
- ✓ Dirt and cloudiness
- ✓ Mold and algae
- ✓ Oxidized iron
- ✓ Oxidized manganese
- ✓ Oxidized sulfides
- ✓ Particles 5 micron and larger in size

(as tested by Everpure)

This drinking water system must be maintained according to the manufacturer's instructions, including replacement of filter cartridges.

The substances reduced or removed by this system are not necessarily in your water. But it is comforting to know that the right Everpure Drinking Water System can handle most any problem.

Read the performance data sheet.

SPECIFICATION:-

Inlet/Outlet	: ½" BSPT
Flow Rate	: Maximum 1.67 gpm (6.3 Lpm)
Working Pressure range	: 10 -125 psi (0.7 – 8.6 bar), non-shock
Temperature	: 35°F - 100°F (2 - 38°C)
Capacity	: 9,000 gallons (34,068L)
Dimension	: 26.5" H x 18" W x 6" D (67cm H x 46cm W x 15.2cm D) (additional 1.5"/4cm clearance height required below the cartridge)

APPLICATIONS:-

- For boiler applications.
- Special problem-solving cartridge.

**NOTE: The contaminants or other substances removed or reduced by this filtration system are not necessarily present in your water.

EVERPURE
WATER YOU CAN TRUST®